

Gram : CENBOSEC, Delhi – 92
E-Mail: cbsecli@nda.vsnl.net.in
website: www.cbse.nic.in



Phone: 22509256-59
Fax: 22515826

CENTRAL BOARD OF SECONDARY EDUCATION

(An Autonomous Organisation under the Union Ministry of Human Resource Development Govt. of India)

“SHIKSHA KENDRA”, 2, COMMUNITY CENTRE, PREET VIHAR, DELHI – 110092

F-47 A/SL/Maint./2012

Dated: 05.12.2012

Sub: Quotation for P&L of Sewer line in the Community Centre & making connection with the existing Manholes

Sir,

The CBSE intends to relay the Sewer line in the Community Centre & the same shall be connected the existing manholes. Reputed agencies which have executed similar civil works may apply on the prescribed format alongwith an EMD of Rs. 1000/- payable through DD/BD in f/o the Secretary, CBSE. The last date for submission of tenders is 14.12.2012 upto 2.00 p.m. The quotations shall be opened on the same day at 2.30 p.m. Incomplete & conditional tenders shall be summarily rejected.

Yours faithfully

(S.K.Sharma)
Superintending Engineer

NAME OF WORK: P&L of Sewer line in the Community Centre & making connection with the existing Manholes

<u>Sl. no.</u>	<u>Item</u>	<u>Qty.</u>	<u>Unit</u>	<u>Rate</u>	<u>Amount</u>
<u>1.</u>	Dismantling of interlocking pavers i/c the sub-grade, excavating upto 0.60 mtr. & making trench for laying of 250 mm dia pipes	15 mtr.	Mtr.		
<u>2.</u>	P&L and jointing galzed stoneware pipes 250mm dia class SP-1 with stiff mixture of C.M. 1:1 i/c testing of joints etc. complete with interconnection to the existing manholes on both ends OR P&L non-pressure NP-2 (light dully) RCC pipes of size 250 mm with collars jointed with stiff mixture of CM 1:2 i/c testing of joints etc. complete with interconnection to the existing manholes on both ends	15 mtr.	Mtr.		
<u>3</u>	P&L of C.C 1:5:10 all-round the S.W. pipes i/c bed concrete	15 mtr.	Mtr.		
<u>4</u>	Constructing of brick-masonry circular manhole 0.91 m internal dia at bottom & 0.56 dia at top in C.M. 1:4 with RCC top slab with 1:2:4, inside plastering 12 mm thick & foundation concrete with 1:4:8 mix. Internal finishing with 1:3 mix & neatly finished with float coat of neat cement as per standard design. {Depth 0.91 with SFRC cover and frame(Heavy duty), HD-20 grade designation} conforming to IS:12592, weight of cover and frame not to be less than 182 kg., fixed in cement concrete 1:2:4 i/c centering, shuttering, all complete With sewer bricks conforming to IS:4885	1	Each one		

Terms & conditions

1. The work shall be executed on holidays/Sunday and ensuring that existing system is not disturbed.
2. The work must conform to the specifications.
3. The workmanship must be excellent.
4. The material shall be got approved from the Engineer-in-charge before installation.
5. The work shall be measured jointly.
6. No running payment shall be made.
7. Once the work is started, it will be completed in one go.

Accepted by me

**Sign. of Prop./Manager
Seal of firm**

Add. _____

Tel./Mob.No. _____
