

Gram : CENBOSEC, Delhi – 92  
E-Mail: [cbsedli@nda.vsnl.net.in](mailto:cbsedli@nda.vsnl.net.in)  
website: [www.cbse.nic.in](http://www.cbse.nic.in)



Phone: 22509256-59  
Fax: 22515826

## CENTRAL BOARD OF SECONDARY EDUCATION

(An Autonomous Organisation under the Union Ministry of Human Resource Development Govt. of India)

“SHIKSHA KENDRA”, 2, COMMUNITY CENTRE, PREET VIHAR, DELHI – 110092

No: F-935-I/AP/

Date: 27.09.2012

.....  
.....  
.....  
.....

Sub:- **Quotation for Aluminium Partition work**

Sir,

The CBSE intends to select a suitable agency for execution of aluminium partition works in its Preet Vihar, Patparganj & Rouse Avenue Bldgs. Experienced agencies which have executed 2-3 similar works in reputed organizations may apply on the prescribed format. Sealed quotations alongwith experience documents & EMD amounting to Rs. 5,000/- may be submitted latest by 09.10.2012 upto 2:30 p.m. and dropped in the tender-box placed at Reception Counter, Shiksha Kendra, 2 Community Centre, Preet Vihar, Delhi. The quotation shall be opened on the same day at 3:00p.m.

Incomplete & Conditional quotations shall be summarily rejected. The Secretary, CBSE reserves the right to reject any or all the quotations without assigning any reason-thereof.

Yours faithfully

(S.K. SHARMA)  
SR. ENGINEER (ESTATE)

**SCHEDULE OF WORK**

<b>S. No.</b>	<b>Description</b>	<b>Qty.</b>	<b>Units</b>	<b>Unit Rate (Rs.)</b>	<b>Amount (Rs.)</b>
<b>1.</b>	<p>Providing and fixing aluminium work for doors, windows, ventilators and partitions with extruded built up standard tubular sections/ appropriate Z sections and other sections of approved make conforming to IS: 733 and IS: 1285, fixed with rawl plugs and screws or with fixing clips, or with expansion hold fasteners including necessary filling up of gaps at junctions, at top, bottom and sides with required PVC/neoprene felt etc. Aluminium sections shall be smooth, rust free, straight, mitred and jointed mechanically wherever required including cleat angle, Aluminium snap beading for glazing/ paneling, C.P. brass/ stainless steel screws, all complete as per architectural drawings and the direction of Engineer-in-charge. (Glazing and paneling to be paid for separately) :</p> <p>(A) Anodised aluminium (anodized transparent or dyed to required shade according to IS: 1868, Minimum anodic coating of grade Ac 15)  <b>OR</b>                      Powder Coated aluminium (minimum thickness of powder coating 50 micron)  <b>OR</b>                      Polyester Powder coated aluminum (minimum thickness of polyester powder coating 50 micron)</p> <p>(B) For shutters of doors, windows &amp; ventilators including providing and fixing hinges/ pivots and making provision for fixing of fittings wherever required including the cost of PVC/ neoprene gasket required (Fittings shall be paid for separately)  <b>OR.</b>                      Powder Coated aluminium (minimum thickness of powder coating 50 micron)  <b>OR</b>                      Polyester Powder coated aluminum (minimum thickness of polyester powder coating 50 micron)</p>	<p align="center"><b>300</b></p> <p align="center"><b>40</b></p>	<p align="center"><b>Kg.</b></p> <p align="center"><b>Kg.</b></p>		
<b>2.</b>	<p>P &amp; F glazing in aluminium door/ window / ventilator shutters/ partitions etc. with gasket etc. complete as per directions of the Engineer-Incharge.</p> <p>(a) With float glass panes of 4.0 mm thickness                      (b) With float glass panes of 5.5 mm thickness                      (c) With float glass panes of 8.0 mm thickness</p>	<p align="center"><b>20</b></p> <p align="center"><b>40</b></p> <p align="center"><b>10</b></p>	<p align="center"><b>Sq.mt.</b></p>		
<b>3.</b>	<p>P &amp; F 12mm thick prelaminated particle board flat pressed three layer or graded wood particle board conforming to IS: 12823 Grade I Type II, in paneling fixed in aluminum doors, windows shutters and partition frames with C.P. brass/ stainless steel screws etc. complete as per architectural drawings and directions of engineer-in-charge.</p> <p>*Pre-laminated particle board with decorative lamination on one side and balancing lamination on other side.  <b>OR</b>                      *Pre-laminated particle board with decorative lamination on both sides</p>	<p align="center"><b>16</b></p>	<p align="center"><b>Sq.mt.</b></p>		

<b>4.</b>	Providing and fixing double glazed hermetically sealed glazing in aluminium windows, ventilators and partition etc. with 6 mm thick clear float glass both side having 12 mm air gap including providing EPDM gasket, perforated aluminium spacers, desiccants, sealant (Both primary and secondary sealant ) etc. as per specifications, drawings and direction of Engineer-in-charge complete.	<b>Rate only</b>	<b>Sq.mt</b>		
<b>5.</b>	P/F diecast special aluminium handles of size 100 mm as approved by the Engineer-in-charge.	<b>2</b>	<b>Each</b>		
<b>6.</b>	P & F aluminium tower bolts ISI marked anodized (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with necessary screws etc. complete: 250x10mm	<b>4</b>	<b>Each</b>		
<b>7.</b>	P & F aluminium sliding door bolts ISI marked anodized (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour or shade with nuts and screws etc. complete: 250x16 mm	<b>2</b>	<b>Each</b>		
<b>8.</b>	P & F IS : 3564 marked aluminium extruded section body tubular type universal hydraulic door closer with double speed adjustment with necessary accessories and screws etc. complete.	<b>2</b>	<b>Each</b>		
<b>9.</b>	P & F aluminium hanging floor door stopper ISI marked anodized (anodic coating not less than grade AC 10 as per IS: 1868) transparent or dyed to required colour and shade with necessary screws etc. complete. Twin rubber stopper	<b>2</b>	<b>Each</b>		

**GROSS AMOUNT:.....**

**Signature:**

**Prop./Manager**

## Terms & Conditions

1. The work shall be executed as per the approved specifications and CPWD norms.
2. The work is Time -Bound, hence time is the essence of the contract.
3. The work is to be completed within one month from 7<sup>th</sup> day of award of work.
4. All the materials shall be got approved from the Engineer-Incharge before installation and the samples shall remain with the Junior Engineer.
5. No T & P shall be provided by the Board.
6. Scaffolding shall be arranged by the Contractor.
7. The work shall be executed under the strict supervision of the Board's J.E. The joinery must be perfect & flush imparting neat finishing without any kinks/ burrs.
8. The measurements shall be recorded jointly.
9. An affidavit certifying five years structural stability i/c anodic / powder coating shall be given on Rs.10/- non-judicial stamp paper duly attested by the Notary Public.
10. The anodic coating must be minimum of AC 15 grade.
11. In case of delay, a penalty @ 1% per week shall be levied subject to a max of 5%.
12. In case of poor workmanship, the Board shall have the right to rescind the contract and get the work executed through any other agency at the risk & cost of the defaulting contractor.
13. In case the work is kept suspended without any valid reason, the Board shall be free to get the remaining work executed through any other agency.
14. The contractor shall be required to provide adequate safety for its workers and the Board shall not be accountable to any kind of injury/ accident at site.
15. 10% amount shall be retained as security for a period of 6 months as defect liability. In case no defect is observed the same shall be released.
16. The quantities are tentative and the agency would be required to undertake similar works on same rate for a minimum period of six (6) months

**Accepted by me**

**Signature  
Prop. /Manager**

