CENTRAL BOARD OF SECONDARY EDUCATION

SHIKSHA KENDRA, 2, COMMUNITY CENTRE, PREET VIHAR, DELHI-92

"SHORT TERM TENDER NOTICE"

The CBSE invites tender under Two-Bid system for providing False - Ceiling at its office premises, 76

G, Sec-18, Gurgaon on urgent basis. Agencies having (5) five years experience & executed 3 works of

equivalent magnitude in reputed organizations need to apply. The False - Ceiling shall be of reputed

make namely; Armstrong/India Gypsum/Boral/Everest Carrier. The estimated cost of the work is Rs.

9.8 lakh. An EMD of Rs. 20,000/- in the form of DD/BD payable in f/o the Secretary CBSE &

experienced documents must be attached with the Technical -Bid. The last date to submit the

tender is 01.11.2013 upto 2.00 p.m. and shall be opened on the same day at 3.00 p.m. Incomplete,

conditional & belated tenders shall be summarily rejected. Tender form & other details be

downloaded through our website: www.cbse.nic.in

Joint Secretary (A&L)

INSTRUCTIONS TO THE TENDERERS

	Mobile No.:
	 Tel. No.:
	Add
	With complete address and seal
	(Signature of the Agency)
8.	Technical Bid received without EMD of Rs.20, 000/- in the form of a Demand draft / Banker's Cheque shall be summarily rejected.
7.	Any additional information required by CBSE in respect of the work experience shall be submitted by the tenderers within three days, failing which the offer shall not be entertained.
6.	The Technical-Bids shall be opened on 01.11.2013 at 3.00 p.m. in the presence of the tenderers, who may like to be present.
5.	Technical Bids and Price-Bid should be signed by the same authorized signatory.
4.	Prescribed enclosures are to be attached with the Technical Bid.
3.	The agency should quote the rates after visiting the site and proper assessment of work.
2.	Rates are to be quoted in words and figures without any cutting/overwriting
1.	Incomplete and conditional tenders shall be summarily rejected.

CENTRAL BOARD OF SECONDARY EDUCATION, 2, COMMUNITY CENTRE, PREET VIHAR, DELHI-92

PART-A Technical-Bid

Name of work : P & F of False - Ceiling

3.1 Contract details fulfilling eligibility criteria

Last Date for submission: 01.11.2013 Upto 2.30 p.m.

Opening of tender: 01.11.2013 on 3.00 p.m.

Locations : Office Premise	es at 76- G, Sec-18, Gurgaon (Haryana)
1. <u>Credentials of tenderer</u>	
1.1 Name of the Agency:	
1.2 Office Address and	
Tel.Nos.	
1.3 Licence No. & Registration	
details(with documentary	
evidence) _	
(With documentary evidence)	
1.4 PAN No.	
(with documentary evidence)	
1.5 Service Tax Regd. Certificate:	
(supported with documentary evidence)	
2. Annual turnover for last three years	
supported with documentary evidence)_	
3. Experience	

S.No.	Year	Name of the	Cost of the work	Officer Concd. in the	Period From To
		Organization	(Executed)	Organization with T.No.	
01.					
02.					
03.					

3.2	. Present	assignment in	n hand

19	ıır	n	ortec	lwith	docu	ment	arv	evide	nce)
v	ԿԻ	יאי	oi icc		uocu		uiy	CVIG	1100)

(i)

(ii)

(iii)

3.3 Manpower details in terms of supervisors, & staff

3.5 Earnest Money Deposit (EMD)

- 1. The Govt. Departments, Public Sector Units, Small Scale Industrial (SSI) Units (only permanently registered) & agencies registered with NSIC etc., are exempted from submitting EMD.
- 2. SSI Units and agencies requesting for exemption from submission of EMD shall submit a copy of their Registration Certificate.

Only such SSI Units and agencies registered for the same trade/Item for which the tender is relevant shall be exempted from submission of EMD.

3.	EMDs of unsuccessful tenders shall be refunded after reasonable time without interest.						
4.	The tenders without EMD or partial EMD shall be summarily rejected.						
5.	Earnest money to successful tenderers shall be returned after submitting the Initial Security Deposit (ISD) @ 10% of contract value in form as prescribed under General Financial Rules, 2005. No interest will accrue on such deposit.						
Parti	iculars of D.D. as Earnest money:						
An	nount Rs.: 20,000/-						
D.I	D/B.D Nos. :						
lss	uing Bank with						
Da	te of Issue:						
5. Th	ne Financial-Bid of the Agencies selected through Technical-Bid shall only be opened.						
Decla	aration: All terms and conditions as mentioned in the tender are acceptable to me/us.						
	(Signature of the Tenderer)						
	With complete address and seal						
Tel. I	No.:						
Mob	ile No.:						
Place	::						
Date	:						

PART -B

Schedule of work

SI.	Description	Qty.	Unit	Rate	Amount
No.					
1.	Providing and fixing false ceiling at all height including providing and fixing of frame work made of special sections, power pressed from M.S. sheets and galvanized with zinc coating of 120 gms/sqm (both side inclusive) as per IS: 277 and consisting of angle cleats of size 25 mm wide x 1.6 mm thick with flanges of 27 mm and 37mm, at 1200 mm centre to centre, one flange fixed to the ceiling with dash fastener 12.5 mm dia x 50mm long with 6mm dia bolts, other flange of cleat fixed to the angle hangers of 25x10x0.50 mm of required length with nuts & bolts of required size and other end of angle hanger fixed with intermediate G.I. channels 45x15x0.9 mm running at the spacing of 1200 mm centre to centre, to which the ceiling section 0.5 mm thick bottom wedge of 80 mm with tapered flanges of 26 mm each having lips of 10.5 mm, at 450 mm centre to centre, shall be fixed in a direction perpendicular to G.I. intermediate channel with connecting clips made out of 2.64 mm dia x 230 mm long G.I. wire at every junction, including fixing perimeter channels 0.5 mm thick 27 mm high having flanges of 20 mm and 30 mm long, the perimeter of ceiling fixed to wall/partition with the help of rawl plugs at 450 mm centre, with 25mm long dry wall screws @ 230 mm interval, including fixing of gypsum board to ceiling section and perimeter channel with the help of dry wall screws of size 3.5 x 25 mm at 230 mm c/c, including jointing and finishing to a flush finish of tapered and square edges of the board with recommended jointing compound , jointing tapes , finishing with jointing compound in 3 layers covering upto 150 mm on both sides of joint and two coats of primer suitable for board, all as per manufacturer's specification and also including the cost of making openings for light fittings, grills, diffusers, cutouts made with frame of perimeter channels suitably fixed, all complete as per drawings, specification and direction of the Engineer in Charge but excluding the cost of painting with:				
	12.5 mm thick tapered edge gypsum moisture resistant Board	300	sqm		
2.	Providing and fixing tiled false ceiling of approved materials of size 595x595 mm in true horizontal level, suspended on inter locking metal grid of hot dipped galvanized steel sections (galvanized @ 120 grams/sqm, both side inclusive) consisting of main "T" runner with suitably spaced joints to get required length and of size 24x38 mm made from 0.30 mm thick (minimum) sheet, spaced at 1200 mm center to center and cross "T" of size 24x25 mm made of 0.30 mm thick(minimum) sheet, 1200 mm long spaced between main "T" at 600 mm center to center to form a grid of 1200x600 mm and secondary cross "T" of length 600 mm and size				

sheet to panel to size 24% approved cutting/n grills, lig "T" runn slotted oceiling of fasteners butterfly mm space bottom educations be pre-pheights a	hm made of 0.30 mm thick (minimum) be interlocked at middle of the 1200x600 mm of form grids of 600x600 mm and wall angle of x24x0.3 mm and laying false ceiling tiles of d texture in the grid including, required making, opening for services like diffusers, that fittings, fixtures, smoke detectors etc. Main there is to be suspended from ceiling using Glacets of size 27 x 37 x 25 x1.6 mm fixed to with 12.5 mm dia and 50 mm long dash s, 4 mm Gl adjustable rods with galvanised level clips of size 85 x 30 x 0.8 and the size of the size of the size with galvanised level clips of size 85 x 30 x 0.8 and the size of the			
3	GI Metal Ceiling Lay in plain Tegular edge Global white color tiles of size 595x595 mm, and 0.5 mm thick with 8 mm drop; made of G I sheet having galvanizing of 100 gms/sqm (both sides inclusive) and electro statically polyester powder coated of thickness 60 microns (minimum), including factory painted after	Rate only	sqm	
2. (bending. GI Metal Ceiling Lay in perforated Tegular edge global white color tiles of size 595x595 mm and 0.5 mm thick with 8 mm drop; made of GI sheet having galvanizing of 100 gms/sqm (both sides inclusive) and 20% perforation area with 1.8 mm dia holes and having NRC (Noise Reduction Coefficient) of 0.5, electro statically polyester powder coated of thickness 60 microns (minimum), including factory painted after bending and perforation, and backed with a black Glass fiber acoustical fleece.	350	sqm	
	OR			
	12.5 mm thick square edge PVC Laminated Gypsum Tile of size 595x595 mm, made of Gypsum plasterboard, manufactured from natural gypsum as per IS 2095 part I and laminated with white 0.16mm thick fire retardant PVC film on the face side and 12micron metalized polyester on the back side with all edges sealed with the face side PVC film which goes around and wraps the edges and is bonded to the edges and the back side metalized polyester film so as to make the tile a completely sealed unit.	350	sqm	
1	12.5 mm thick fully Perforated Gypsum Board tile made from plasterboard having glass fibre conforming to IS: 2095 part I, of size 595x595 mm, having perforation of 9.7x9.7 mm at 19.4 mm c/c with center borders of 48 mm and the side borders of 30 mm, backed with non woven tissue on the back side, having an NRC (Noise	350	sqm	

	Reduction Coefficient) of 0.79, with 50 mm			
	resin bonded glass wool backing.			
	room boridod glado woor backing.			
	OR			
600x6 fixing mm th room at 300 carried thick 37x27 and C at 100 having steel 0 and in with h carried conne galvar	ling and fixing GI Clip in Metal Ceiling System of 00 mm module which includes providing and 'C' wall angle of size 20x30x20 mm made of 0.5 nick pre painted steel along the perimeter of the with help of nylon sleeves and wooden screws 0 mm center to centre, suspending the main C of size 10x38x10 mm made of G.I steel 0.7 mm from the soffit with help of soffit cleat x25x1.6 mm, rawl plugs of size 38x12 mm carrier suspension clip and main carrier bracket 20 mm c/c. Inverted triangle shaped Spring Tee 30 height of 24 mm and width of 34 mm made of Gl 0.45 mm thick is then fixed to the main C carrier direction perpendicular to it at 600 mm centers elp of suspension brackets. Wherever the main C of and spring T have to join, C carrier and spring T ctors have to be used. All sections to be nized @ 120 gms/sqm (both side inclusive), fixing ip in tiles into spring 'T' with:			
2.	GI Metal Ceiling Clip in plain Beveled edge global white color tiles of size 600x600 and 0.5 mm thick with 25 mm height, made of G I sheet having galvanizing of 100 gms/sqm (both sides inclusive) and electro statically polyester powder coated of thickness 60 microns (minimum), including factory painted after bending. GI Metal Ceiling Clip in plain Beveled edge global white color tiles of size 600x600 and 0.5 mm thick with 25 mm height, made of G I sheet having galvanizing of 100 gms/ sqm (both sides inclusive) and 20% perforation area with 1.8 mm dia holes and having NRC of 0.5, electro statically polyester powder coated of thickness 60 microns (minimum), including factory painted after bending and perforation.	350 25	sqm	

With complete address and seal

Add._____

(Signature of the Agency)

Tel. No.:_____

Mobile No.:_____

Terms and Conditions

- 1. The work should be executed as per CPWD specifications and as per directions of Engineer-In-Charge.
- 2. The Completion time would be 15 days.
- 3. In case of delay, a penalty of 2% per week shall be deducted subjected to a max. of 5% of the tender value.
- 4. The measurement shall be done jointly by the Contractor and the Board's Engineer.
- 5. All T & P shall be arranged by the Contractor.
- 6. Hindrance Register shall be maintained at site.
- 7. Instructions given in Site Order Book would be followed immediately.
- 8. Final bill would be paid within 30 days after submission of Bill by the Contractor.
- 9. 10% of the bill shall be deducted as defect liability and shall be released after one year.
- 10. 25% deviation in quantities would be permitted.
- 11. Extra-item if any would be paid on analyzed Market rates but the work must be executed with prior approval of Engineer-in-charge.
- 12. In case of any dispute, the Arbitrator shall be appointed by the Chairman and his decision shall be binding.
- 13. The materials to be used must be got approved from the Engineer-in-charge before installation/use.
- 14. The agency shall not delay/stop the work without any valid reason.
- 15. In case of no/slow progress, the Board shall have the right to rescind the contract & get the work executed at the risk & cost of the defaulting agency.
- 16. Any material to be used on site shall be got checked & approved through the Engineer-In-Charge.

(Sig	nature of the Agency)
With com	plete address and seal
Add	•
Tel. No.:	:
Mobile No.:	